



BULLETIN # 10T-01

Carlyle Compressor Division
PO Box 4808
Carrier Parkway, Bldg. TR4
Syracuse, NY 13221

SUBJECT: Solutions Version 4.1 Release

DATE: April 25th, 2010

AUTHOR: John Byrnes

<input checked="" type="checkbox"/> PRODUCT	<input type="checkbox"/> SERVICE & PARTS	<input type="checkbox"/> GENERAL
---	--	----------------------------------

Product Name: Solutions Performance Estimation Software Version 4.1

DESCRIPTION

Carlyle is announcing the release of Carlyle Solutions Version 4.1. This version includes expanded medium temperature performance data for certain 06DR models applied with R-407A. The list of models included in this announcement is identical to the list of 06DR models that may be applied at an expanded medium temperature range with R-22. The asterisks in the final 3 digits of the model numbers below indicate voltage and packaging specifics.

06DR3160CA3***	06DR2280DA3***	06DR8200DA3***
06DR3370DA3***	06DR7250DA3***	06DR5410DA3***

This release also adds performance estimates for several obsolete 06D and 06CC models with R-407A (base model numbers shown below). Service replacement equivalents for these models are still available through Carrier-Authorized Distribution.

06DR724#	06CC016#
06DA824#	06CC018#

For additional information related to R-407A application requirements refer to Carlyle Bulletin 09T-03.

APPROVED APPLICATION RANGES

06DR- Low Temperature Models¹

- SST = -35° F to 25° F
- SDT = 70° F to 120° F

1. Only the above listed 06DR models are approved for the expanded 0° F to 25° F Suction Temperature range.

Feel free to contact Application Engineering at 800-GO-CARLYLE (800-462-2759) if you have any questions related to this bulletin.